

BRUSH CUTTERS

TWISTER F2



The Stinger Attachments Twister F2 Brush Cutter is a standard general duty cutter designed for small to medium size machines. It is rated for up to 4" material and works well for general property maintenance to aid in controlling or cleaning up tall grass, weeds, and small brush. The Twister F2 cutter utilizes a direct drive Geroler motor for long term reliability and requires 10-27 gpm hydraulic flow. The Stinger

Attachments Twister F2 Brush Cutter is built in the USA with high quality materials and workmanship for reliability to get the job done.

FEATURES

- 865-965#
- 4" Cut Capacity
- 3/16 thick deck (1/4" sides)
- 2 Blade Holder
- 1/2" Blade Holder Thickness (Hardened)
- 775-925 RPM
- Geroler Motor
- Direct Drive
- Flow Required – 10-27 gpm
- No Case Drain Required
- 1 Year Warranty



PROPER BALLAST REQUIRED FOR ALL.

TWISTER F3



The Stinger Attachments Twister F3 Brush Cutter is a heavy-duty cutter designed for medium to large size machines. It is rated for up to 6" material and works well for general property maintenance to aid in controlling or cleaning up tall grass, weeds, and large brush. The Twister F3 cutter utilizes a direct drive Geroler motor for long term reliability. The standard flow

requires 15-25 gpm and the high flow requires 25-35 gpm hydraulic flow. It is offered in standard or high flow. The Stinger Attachments Twister F3 Brush Cutter is built in the USA with high quality materials and workmanship for reliability to get the job

FEATURES

- 1400-1850#
- 6" Cut Capacity
- 1/4 thick deck (1/4" sides)
- 3 Blade Holder
- 5/8" Blade Holder Thickness (AR400)
- 725-925 RPM
- Geroler Motor
- Direct Drive
- Flow Required
- Standard Flow 15-25 gpm
- High Flow 25-35 gpm
- No Case Drain Required-Standard Flow
- Case Drain Required-High Flow
- 1 Year Warranty



Contact us for further details!

(507) 273-7497
www.stingerattachments.com

61441 170th Street,
Rose Creek, MN 55970

Twister F3 Hybrid



The Stinger Attachments Twister F3 Hybrid Brush Cutter is a commercial duty cutter designed for medium to large size machines. It is rated for up to 7" material and works well for general property maintenance to aid in controlling or cleaning up tall grass, weeds, and large brush. The Twister F3 Hybrid features a heavier blade holder of the Twister F4 in the frame of the Twister F3 for increased strength without the need of a case drain. The Twister F3 Hybrid cutter utilizes a direct drive Geroler motor for long term reliability and requires 15-25 gpm

hydraulic flow. The Stinger Attachments Twister F3 Hybrid Brush Cutter is built in the USA with high quality materials and workmanship for reliability to get the job done.

FEATURES

- 1550-2000#
- 7" Cut Capacity
- 1/4 thick deck (1/4" sides)
- 3 Blade Holder 60"
- 4 Blade Holder 72" & 78"
- 5/8" Blade Holder Thickness (AR400)
- 725-925 RPM
- Geroler Motor
- Direct Drive
- Flow Required – 15-25 gpm
- No Case Drain Required
- 1 Year Warranty



Twister F4



The Stinger Attachments Twister F4 Brush Cutter is a heavy-duty commercial cutter designed for large size machines. It is rated for up to 7" material and works well for general property maintenance to aid in controlling or cleaning up tall grass, weeds, and large brush. The Twister F4 cutter utilizes a direct drive Gear/Piston motor for long term reliability and requires 17-45 gpm hydraulic flow. The Stinger Attachments Twister F4 Brush Cutter is built in the

USA with high quality materials and workmanship for reliability to get the job done.

FEATURES

- 1550-2000#
- 7" Cut Capacity
- 1/4 thick deck (5/16" sides)
- 3 Blade Holder
- 4 Blade Holder 72" & 78"
- 5/8" Blade Holder Thickness (AR400)
- 725-925 RPM
- Gear/Piston Motor
- Direct Drive
- Flow Required – 17-45 gpm
- Case Drain Required
- 1 Year Warranty



Twister F5



The Stinger Attachments Twister F5 Brush Cutter is an extreme-duty commercial cutter designed for large size machines. It is rated for up to 10" material and works well for tough jobs to aid in controlling or cleaning up tall grass, weeds, and large brush. The Twister F5 cutter utilizes a direct drive Piston motor for long term reliability and requires 17-45 gpm (standard) or 25-45 gpm (high) hydraulic flow.

The Twister F5 cutter utilizes a direct drive Piston motor for long term reliability and requires 17-45 gpm (standard) or 25-45 gpm (high) hydraulic flow.

The Stinger Attachments Twister F5 Brush Cutter is

built in the USA with high quality materials and workmanship for reliability to get the toughest jobs done.

FEATURES

- 2500-2600#
- 10" Cut Capacity
- 3/8 thick deck (1/2" sides)
- 3 Blade Holder
- 4 Blade Holder 72" & 78"
- 1" Blade Holder Thickness
- 775-925 RPM
- Piston Motor
- Direct Drive
- Flow Required
- Standard Flow 17-45 gpm
- High Flow 25-45 gpm
- Case Drain Required
- 1 Year Warranty



Contact us for further details!

(507) 273-7497

www.stingerattachments.com

61441 170th Street,
Rose Creek, MN 55970