



## FEATURES:

- Grade 50 Steel
- 4" x 4"x ¼" Top Tubing
- 3" x 3" x ¼" Bottom Tubing
- 3/8" One-Piece Flat Tines
- 6-3/8" Tine Spacing (6" opening)
- ½" Grapple Supports and Grapple Frames
- 45" Grapple Opening
- Twin 3000 PSI Cylinders
- ½" Flat Faced Couplers
- ½" Serrated Cutting Edge
- 2 Year Warranty



## **OPTIONS:**

- Universal Quick Attach Carrier
- Global Carrier

SIZES:

■ **78"** ■ **84"** ■ 91"

The Stinger Attachments RTG-XD Series Root Grapple is designed for larger horsepower machines. This utilizes 1/2" material throughout with a 6" tinie spacing to capture parge debris. This bucket features a flat-tine design that works well to get under debris. The open side design allows the operator to secure and move longer debris. This grapple is fitted with 2 grapples that operate independently to confidently secure an uneven load. This grapple is built with the strongest backbone in the industry, featuring a 1-piece tine design that is welded around a 3"x 3" lower backbone. This design adds considerable strength and life over the more common 2-piece welded tine utilized in most other brands.

PROPER BLAST REQUIRED

**Contact us for further details!** 

(507) 273-7497 www.stingerattachments.com

